



illumination design  
SINCE 1972



# TECHNICAL SHEETS





illumination design  
SINCE 1972



# TECHNICAL SHEETS

21403










MATERIALI / MATERIALS	
Struttura / Frame	Acciaio / Steel
Vetro / Glass	Pirex (vetro borosilicato temperato) / Pirex (tempered borosilicate glass)

DATI TECNICI / TECHNICAL DATA		
INFO	EUROPE	USA
Prodotto / Product	Lampadario / Chandelier	Lampadario / Chandelier
Installazione / Installation	Soffitto / Ceiling	Soffitto / Ceiling
Diametro / Diameter	92 cm.	36,22"
Altezza / Height	15 cm.	5,90"
Cavi Standard / Standard wires	130 cm.	51,18"
Rosone / Canopy	Ø 24 cm.	Ø 9,44"

SPECIFICHE ELETTRICHE / ELECTRICAL SPECIFICATIONS		
INFO	EUROPE	USA
Alimentazione / Power Supply	220-240V – 50/60Hz	100-120V – 50/60Hz
Specifiche lampade/Bulbs specifications	85W Strip led 4000K (incl. / incl.)	85W Strip led 4000K (incl. / incl.)
Wattaggio massimo / Max wattage	85W (9180 lumen)	85W (9180 lumen)
Tensione led / led voltage	24VDC (driver incl. / driver incl.)	24VDC (driver incl. / driver incl.)
Dimmerabilità / Dimmability	Phase dimming on request	Phase dimming on request

OPZIONE DECORI STANDARD / STANDARD FINISHING OPTIONS	Opzioni vetri / Glass options
 <p>nickel / nickel</p>	 <p>Bianco opaco / Mat white</p>

PESO E VOLUME / WEIGHT AND VOLUME		
 <p>Peso Netto / Net weight Kg.12,00</p>	 <p>Volume M3 0,300</p>	 <p>Peso Lordo / Gross weight Kg.15,00</p>

--- MADE IN ITALY ---